











Reflective Tape Properties

REFLECTIVE TAPE	Backing	Domestic or Industrial wash
 XM-6005B PRO	 Poly 500 Anti Fray	 EN 20471 EN 469

Care Instructions

	Wash	Machine Wash Hot, 75°C
	Bleach	Do not bleach
	Dry	Tumble Dry Low
	Dry-clean	Dry clean, PCE (Petroleum Solvent) only
	Iron	Iron at low temperature, 110°C

Method of Application

Please contact us for instructions or check our web-site.

Important Notice

Type of work environment, exposure conditions and maintenance have an impact on reflective performance. Please test each tape according to appropriate care instructions required for the garment.

High-visibility clothing made with reflective material should be maintained in good condition and inspected regularly for damage or deterioration.

Description

Silver reflective tape with Anti Fraying properties is designed for the toughest use. Made of enforced polyester this reflective tape does not fray on the edges even after 60 industrial washes. High grade micro-breads reflects the light with more power thus providing high visibility of building workers, road workers and other professionals. Durable and easy to care reflective tape for the best HighVis clothing.

Product Construction

This Reflective Material is a Polyester Fabric coated with a layer of resin with numerous glass micro-lenses impregnated with a special glue into this layer. The light reflects from these micro-lenses and comes back to a car (or other sources of light) making the person wearing reflective tape more visible in the dark.

Product Detailed Information

Material	100% Polyester
Finish	-
Colour	Silver
Industrial wash	Allowed
Roll, Width	50 mm
Roll, Length	100 meters
Roll, Weight	1.6 kgs

Product Certifications

NFPA 2112	-
ANSI 107	50×60°C ISO 6330
CSA Z96 (Level 2)	50×60°C ISO 6330
EN 20471	60×75°C ISO 15797, 30x dry clean ISO 3175
EN 469	-
EN 15384	-
OEKO-TEX 100	Class 2
Certificate of Test	Aitex (Spain) , UL (USA)

Shelf Life

Keep in cool dry place, with no direct sunlight. Use the product during 12 months from the date of purchase.