











## Reflective Tape Properties

REFLECTIVE TAPE	Backing	EN 20471	EN 469	Domestic or Industrial wash
<b>XM-6005B</b>	TC 500 Industrial			

## Care Instructions

	Wash	Machine Wash Hot, 75°C
	Bleach	Do not bleach
	Dry	Tumble Dry Low
	Dry-clean	Dry clean, PCE (Petroleum Solvent) only
	Iron	Iron at low temperature, 110°C

## Method of Application

Please contact us for instructions or check our web-site.

## Important Notice

Type of work environment, exposure conditions and maintenance have an impact on reflective performance. Please test each tape according to appropriate care instructions required for the garment.

High-visibility clothing made with reflective material should be maintained in good condition and inspected regularly for damage or deterioration.

## Description

Silver reflective tape with superior retro-reflective performance is best suited for Heavy duty EN 20471 workwear. It is made with polycotton backing. Maximum retroreflection is guaranteed even after numerous Industrial laundry cycles. High grade micro-beads provides extra visibility of workers. Available in 1", 2", 3", 4" width.

## Product Construction

This Reflective Material is a Poly-cotton Fabric coated with a layer of resin with numerous glass micro-lenses impregnated with a special glue into this layer. The light reflects from these micro-lenses and comes back to a car (or other source of light) making the person wearing reflective tape more visible in the dark.

## Product Detailed Information

Material	65% Polyester, 35% Cotton
Finish	-
Colour	Silver
Industrial wash	Allowed
Roll, Width	50 mm
Roll, Length	100 meters
Roll, Weight	1.6 kgs

## Product Certifications

NFPA 2112	-
ANSI 107	50×60°C ISO 6330
CSA Z96 (Level 2)	50×60°C ISO 6330
EN 20471	50×75°C ISO 15797, 50x dry clean ISO 3175
EN 469	-
EN 15384	-
OEKO-TEX 100	Class 2
Certificate of Test	Aitex (Spain) , UL (USA)

## Shelf Life

Keep in cool dry place, with no direct sunlight. Use the product during 12 months from the date of purchase.