# Colour Reflective Tape & Piping | Sew-on





#### Care Instructions

| 75             | Wash      | Machine Wash Hot, 75°C                  |
|----------------|-----------|-----------------------------------------|
| X              | Bleach    | Do not bleach                           |
| $\odot$        | Dry       | Tumble Dry Low                          |
| P              | Dry-clean | Dry clean, PCE (Petroleum Solvent) only |
| $\overline{a}$ | Iron      | Iron at low temperature, 110°C          |

## Method of Application

Please contact us for instructions or check our web-site.

## Important Notice

Type of work environment, exposure conditions and maintanance have an impact on reflective performance. Please test eah tape according to appropriate care instructions requires for the garment.

High-visibility clothing made with reflective material should be maintained in good condition and inspected regularly for damage or deterioration.

## Description

Yellow/Orange-Silver and grossgrain reflective ribbon trim becomes very popular for safety vests. It is made with high-grade reflective tape thermo-transferred onto colour grossgrain backing. The trim lets you customize your work clothing and increase safety of workers. You may choose the width of Silver stripe as well as the width and colour of backing.

#### Product Construction

This Reflective Material is a Polyester Fabric coated with a layer of resin with numerous glass micro-lenses impregnated with a special glue into this layer. The light reflects from these micro-lenses and comes back to a car (or other source of light) making the person wearing reflective tape more visual in the dark.

#### Product Detailed Information

| Material        | 100% Polyester |
|-----------------|----------------|
| Finish          | -              |
| Colour          | Yellow-Silver  |
| Industrial wash | Allowed        |
| Roll, Width     | 50 mm          |
| Roll, Length    | 100 meters     |
| Roll, Weight    | 2.05 kgs       |

#### **Product Certifications**

| NFPA 2112           | -                       |
|---------------------|-------------------------|
| ANSI 107            | 50×60°C ISO 6330        |
| CSA Z96 (Level 2)   | 50×60°C ISO 6330        |
| EN 20471            | 50×75°C ISO 15797       |
| EN 469              | -                       |
| EN 15384            | -                       |
| OEKO-TEX 100        | -                       |
| Certificate of Test | Aitex (Spain), UL (USA) |

## Shelf Life

Keep in cool dry place, with no direct sunlight. Use the product during 12 months from the date of purchase.



XM TEXTILES EUROPE

Dariaus ir Gireno st.42A Room 509, Vilnius LT-02189, Lithuania

**3** +370 52 078 703

info@xmtextiles.com
www.xmtextiles.com

XM TEXTILES ROMANIA

Sos.Tamasi 20, Hala 6B Parter, Buftea 070000, Ilfov, Romania

\*\* +40 31 630 3639 info@xmtextiles.com

info@xmtextiles.com
www.xmtextiles.com

XM TEXTILES USA LLC

17350 State Hwy 249
Ste 220 #12586
Houston, TX 77064, USA
+1 737 400 0288

info@xmtextiles.com

www.xmtextiles.com