



Description

Reflective tape XM-8011 in Silver colour with FR properties. Designed for Heat Transfer application on FR-workwear and Firefighters clothing. XM-8011 is a high-tech material and its adhesive properties varies depending on type of fr fabric. We advise you before the first use to check the grip of the tape by applying it on a certain FR-clothing. It is also useful to make trial washes of fr-clothing with applied reflective tape.

Product Construction

This Reflective Material is a PU+Polyester resin with numerous glass micro-lenses impregnated into adhesive layer and placed on a film liner. The light reflects from these micro-lenses and comes back to a car (or other sources of light) making the person wearing reflective tape more visible in the dark.

Product Detailed Information

| | |
|-----------------|-----------------|
| Material | FR PU+Polyester |
| Finish | Flame retardant |
| Colour | Silver |
| Industrial wash | - |
| Roll, Width | 50 mm |
| Roll, Length | 100 meters |
| Roll, Weight | 2.35 kgs |

Product Certifications

| | |
|---------------------|------------------|
| EN 20471 | 50×60°C ISO 6330 |
| EN 469 | 50×60°C ISO 6330 |
| EN 15384 | 50×60°C ISO 6330 |
| NFPA 2112 | UL (USA) |
| NBR 15292 | - |
| OEKO-TEX 100 | Class 2 |
| Certificate of Test | Aitex (Spain) |

Care Instructions

| | | |
|--|-----------|--------------------------------|
| | Wash | Machine Wash Warm, 60°C |
| | Bleach | Do not bleach |
| | Dry | Tumble Dry Low, 55°C |
| | Dry-clean | Do not dry clean |
| | Iron | Iron at low temperature, 110°C |

Important Notice

Type of work environment, exposure conditions and maintenance have an impact on reflective performance. Please test each tape according to appropriate care instructions required for the garment.

High-visibility clothing made with reflective material should be maintained in good condition and inspected regularly for damage or deterioration.

Method of Application

Please contact us for instructions or check our web-site.

Shelf Life

Keep in cool dry place, with no direct sunlight. Use the product during 12 months from the date of purchase.