



Care Instructions

40	Wash	Machine Wash Warm, 40°C
X	Bleach	Do not bleach
\odot	Dry	Tumble Dry Low, 55°C
\boxtimes	Dry-clean	Do not dry clean
	Iron	Iron at low temperature, 110°C
		,

Important Notice

Type of work environment, exposure conditions and maintanance have an impact on reflective performance. Please test eah tape according to appropriate care instructions requires for the garment.

High-visibility clothing made with reflective material should be maintained in good condition and inspected regularly for damage or deterioration.

Description

Reflective tape XM-8012 in Orange-Silver colour with Flame Resistant properties. Designed for Heat Transfer application on FR-workwear and Firefighters clothing.

Product Construction

HT FR (Heat Transfer Flame Retardant) films have solid design with less breathability properties then HT Segmented. Yet, even HT films are more flexible and lighter then sew-on Reflective tapes.

Product Detailed Information

Material	FR PU+Polyester
Finish	Flame retardant
Colour	Orange-Silver
Reflectivity, R	490 cd/m ²
Industrial wash	-
Roll, Width	50 mm
Roll, Length	100 meters
Roll, Weight	2.8 kgs

Product Certifications

EN 20471	-
EN 469	-
NFPA 2112	-
NFPA 1971	-
NBR 15292	-
OEKO-TEX 100	Class 2
Certificate of Test	-

Method of Application

Please contact us for instructions or check our web-site.

Shelf Life

Keep in cool dry place, with no direct sunlight. Use the product during 12 months from the date of purchase.



XM Textiles Europe

Dariaus ir Gireno st. 42A, Vilnius, Lithuania, LT-02189

a +370 (5) 207 8703

info@xmtextiles.com

www.xmsilverline.com

XM Textiles Asia

88 Guangxin road, office 2403 Shanghai, China, ZIP 200061

8 +86 (21) 5240-1156

info@xmtextiles.com

www.xmsilverline.com