



Care Instructions

| 40 | Wash | Machine Wash Warm, 40°C |
|----------------|-----------|--------------------------------|
| X | Bleach | Do not bleach |
| \odot | Dry | Tumble Dry Low, 55°C |
| \boxtimes | Dry-clean | Do not dry clean |
| \overline{a} | Iron | Iron at low temperature, 110°C |

Method of Application

Please contact us for instructions or check our web-site.

Important Notice

Type of work environment, exposure conditions and maintanance have an impact on reflective performance. Please test eah tape according to appropriate care instructions requires for the garment.

High-visibility clothing made with reflective material should be maintained in good condition and inspected regularly for damage or deterioration.

Description

Reflective tape XM-8104/10 in Yellow colour with Flame Resistant properties. Designed for Heat Transfer application on FR-workwear and Firefighters clothing. XM-8104/10 is a high-tech material and its adhesive properties varies depending on type of fr fabric. We advise you before the first use to check the grip of the tape by applying it on a certain FR-clothing. It is also useful to make trial washes of fr-clothing with applied reflective

Product Construction

This Reflective Material is a PU+Polyester resin with numerous glass micro-lenses impregnated into adhesive layer and placed on a film liner. The light reflects from these micro-lenses and comes back to a car (or other source of light) making the person wearing reflective tape more visible in the dark.

Product Detailed Information

| Material | FR PU+Polyester |
|-----------------|-----------------|
| Finish | Flame retardant |
| Colour | Yellow |
| Industrial wash | - |
| Roll, Width | 50 mm |
| Roll, Length | 100 meters |
| Roll, Weight | 2.715 kgs |

Product Certifications

| NFPA 2112 | UL (USA) |
|---------------------|---------------------------|
| ANSI 107 | - |
| CSA Z96 | - |
| EN 20471 | 80×40°C, 50×60°C ISO 6330 |
| EN 469 | 80×40°C, 35×60°C ISO 6330 |
| EN 15384 | 80×40°C, 35x60°C ISO 6330 |
| OEKO-TEX 100 | Class 2 |
| Certificate of Test | Aitex (Spain), UL (USA) |

Shelf Life

Keep in cool dry place, with no direct sunlight. Use the product during 12 months from the date of purchase.



XM TEXTILES EUROPE

Dariaus ir Gireno st.42A Room 509 Vilnius LT-02189, Lithuania

3 +370 52 078 703

info@xmtextiles.com www.xmtextiles.com XM TEXTILES ROMANIA

Sos. Tamasi 20, Hala 6B Parter Ruftea 070000, Ilfov, Romania

***** +40.31.630.3639 info@xmtextiles.com

www.xmtextiles.com

XM TEXTILES ITALIA SRL

Via dei Notai, Blocco 23, Centergross 40050 Funo di Argelato (BO) Bologna, Italy

3 +39 051 952 8202

info@xmtextiles.com

www.xmtextiles.com