



Product name	TS-100 Seam Sealing Tape
Type	single-layer hot-melt seam sealing tape
Composition	PVC film + PU adhesive
Thickness	0.12 mm
Width	20 mm
Roll length	200 m
Colours	Transparent
Certification	–
Area of use	sealing of stitched seams on PU- and PVC-coated fabrics: rainwear, waterproof workwear, outdoor gear, footwear and children's products

Physical properties*

	Value
Base film	PVC
Adhesive	PU (hot-melt)
Total thickness, mm	0.12
Layer structure, mm	PVC 0.10 + PU 0.02

Recommended application settings*

	Value
Hot air temperature, °C	400 – 450
Pressure, kg/cm ²	2
Speed, m/min	5 – 10

* The values shown are indicative and may vary slightly from batch to batch.

www.xmtextiles.com

XM TEXTILES EUROPE

Dariaus ir Gireno st. 42A, Room 509
Vilnius, LT-02189, Lithuania
Tel. +370 52 078 703
info@xmtextiles.com

XM TEXTILES ROMANIA

Sos.Tamasi 20, Hala 6B, Parter,
Buftea, 070000, Ilfov, Romania
Tel. +40 31 630 3639
info@xmtextiles.com

XM TEXTILES ITALIA SRL

Via dei Notai, Blocco 23, Centergross,
40050 Funo di Argelato (BO), Bologna, Italy
Tel. +39 051 952 8202
info@xmtextiles.com